

PARAMETRY PIL řady "A, AS"

PILA	Velikost	Hmotnost	Délka řezu při max. hloubce řezu	Délka řezu při dané hloubce	Výkon motoru	Napětí	Otáčky	Kotouč
	dxšxv (mm)		kg	mm				
PKH35A81	1240x720x1310/720	94	630/105	700/20	2,2/3	230/400	2800	350/25,4 (30)
PKH35A100	1460x720x1310/720	108	820/105	900/20	2,2/3	230/400	2800	350/25,4(30)
PKH35A120	1740x720x1310/750	116	1040/105	1100/20	2,2/3	230/400	2800	350/25,4 (30)
PKH35A150	2040x720x1310/750	136	1340/105	1400/20	2,2/3	230/400	2800	350/25,4 (30)
PKH30A81S	1240x710x1310/750	99	650/80	700/20	2,2/3	230/400	2800	300/25,4(30)
PKH30A120S	1650x710x1310/750	121	1050/80	1100/20	2,2/3	230/400	2800	300/25,4(30)
PKH30A150S	1940x710x1310/770	139	1330/80	1400/20	2,2/3	230/400	2800	300/25,4(30)
PKH35A81S	1240x710x1310/750	99	650/80	700/20	2,2/3	230/400	2800	350/25,4(30)
PKH35A120S	1650x710x1310/750	121	1050/80	1100/20	2,2/3	230/400	2800	350/25,4(30)
PKH35A150S	1940x710x1310/770	139	1330/80	1400/20	2,2/3	230/400	2800	350/25,4(30)