

PARAMETRY PIL řady "L4, L6, L9 "

PILA	Velikost	Hmotnost	Délka řezu při max. hloubce řezu	Délka řezu při dané hloubce	Výkon motoru	Napětí	Otáčky	Kotouč
	dxšxv (mm)	kg	mm	mm	kW	V~	1/min	mm
PKH20L4,	730x460x370	21	330/45	360/10	0,8	230	2860	200/25,4
PKH20L6	920x460x1085/370	31	490/45	520/10	0,8	230	2860	200/25,4
PKH20L9	1285x460x1085/415	41	800/45	830/10	0,8	230	2860	200/25,4

PARAMETRY PIL PKH25A60, A51, A101,

PKH25A60	1030x605x1230/530	45	490/65	540/20	1,1	230	2860	250/25,4
PKH23A51	920x560x1190/490	41	410/55	440/20	0,8	230	2860	230/25,4
PKH25A101	1400x605x1240/580	54	890/65	930/20	1,1	230	2860	250/25,4

PARAMETRY PIL PKH25A74MA, A101MA

PKH25A74MA	1140x640x1260/610	56	660/55	700/20	1,8	230	2800	250/25,4
PKH25A101MA	1400x640x1260/610	62	910/55	950/20	1,8	230	2800	250/25,4