

PARAMETRY PIL PK100N, PK60DS, řada PK70 . .

PILA	Velikost	Hmotnost	Délka řezu při max. hloubce řezu	Délka řezu při dané hloubce	Výkon motoru	Napětí	Otáčky	Kotouč
	dxšxv (mm)	kg	mm	mm	kW	V~	1/min	mm
PK60DS	1400x700x1550	183	530/220	530/100	5,5	400	1600	600/25,4
PK100DSD	1930x950x1750	326	530/420	710/100	9	400	1030	1000/60
PK100N1	1930x970x1720	306	530/420	710/100	9	400	1030	1000/60
PK70N2, NPN2	1340x870x1550	122(134)	400/260	460/120	4	400	1400	700/30
PK70NPLN2	1560x870x1550	140	530/260	540/120	4	400	1400	700/30
PK70C2	1340x870x1370	144	400/260	460/120	4	400	1400	700/30
PK70R2N2	1350x870x1430	149	400/280	460/120	5,5	400	1400	700/25,4
PK70Ne	1340x930x1370	166	400/260	460/120	5,5	400	1400	700/30
PK70/90R	1890x860x1590	205	545/260 - ø700 520/360 - ø900	545/100 - ø700 580/100 - ø900	7,5	400	1420(1090)	700(900)/30
PK70RG	1470x852x1490	177	400/280	460/100	5,5	400	1400	700/25,4